Ultrasonic Homogenizer Q700

The Q700 is the most technologically advanced sonicator available today. A state-of-the-art touch screen interface offers intuitive control and provides a user-friendly experience. The most important feature of a Sonicator is reproducibility. Improved internal circuitry guarantees more efficient operation, sample-to-sample consistency and most importantly, a reliable end result.

The Q700 is the only sonicator on the market that offers full amplitude control from 1-100%. This enables greater control of the probe's intensity, helping to pinpoint the optimum settings for efficient sample processing. We have increased maximum power output to 700 watts making the system more durable and capable of handling even larger samples if necessary. Our new display, design improvements and added accessories make this the most sophisticated and versatile Sonicator available today.

Ultrasonic Homogenizer Q700 Features

• Full Amplitude Control

Full amplitude control Amplitude (intensity) is controlled from 1-100% giving a greater degree of resolution and the ability to pinpoint the amplitude needed to effectively process your sample.

• Programmability

Parameters including processing times, pulse on/off and amplitude can be saved to memory and run by the touch of a button.

• Pulse Mode

Adjustable pulse On and Off times to reduce the heat gain in temperature sensitive samples.

• Temperature Monitoring

An optional temperature probe is available for those customers who wish to monitor the temperature of their sample. If the temperature limit is reached, sonication shuts down to prevent overheating.

• RoHS Compliant

All Qsonica equipment is built lead free.

• Run Multiple Programs In Sequence

Multiple programs can be run in sequence. For example, the unit can be programmed to sonicate at 50% amplitude for 5 minutes, shut off for 2 minutes and re-start at 25% amplitude for 10 minutes. Up to 5 programs can be run in succession.

• Total Energy Output Display

Energy delivered to the probe is displayed in both Watts and Joules.

Auto Tuning

The Sonicator digitally tracks frequency changes in the converter / tip assembly caused by load and temperature changes and maintains electrical efficiency at all times. Manual tuning is unnecessary.

• Overload Protection

The unit is equipped with fault detection circuitry to shut down sonication in the event that a fault occurs.

1Page

• Touch Screen Control

A large, color LCD screen clearly displays all operating parameters and options. Intuitively and quickly access any of the Sonicator's functions with a simple touch.

Ultrasonic Homogenizer Q700 Parts

- Generator
- Converter
- 1/2" diameter probe
- Power cable
- Converter cable
- Wrench set

Ultrasonic Homogenizer Q700 Specifications

	Power Rating		700 Watts
	Frequency		20 kHz
d	Programmability	10	Memories Plus Sequencing
7	Programmable Timer		72 Hours
	Adjustable Pulse On/Off		1 Second to 24 Hours
	Dimensions		8" W x 15.25" L x 8.5" H
	Voltage		110V, 50/60Hz

Mehrgan Parto Shar 2Page