9020 TOUCH (6000ml tank)

Page 1



Ultrasonic cleaners function by producing sound waves that are transmitted into the tank and cleaning solution. These waves create millions of microscopic bubbles, which collapse or 'implode', releasing large amounts of energy, which scrub the surface clean. This process is called 'Cavitation'. These tiny bubbles create incredible cleaning results not only to the surface, but by penetrating the finer detail and recesses in surgical instruments and small items to ensure a professional clean prior to disinfection. The **9020 TOUCH** professional cleaner has two ultrasonic transducers to enable uniform distribution of ultrasonic waves. The touch screen control panel of the **9020 TOUCH** has a simple to use **1** to 30 minute full range digital timer. Set your required cleaning time and temperature and let the cleaner do the hard work for you. The **9020 TOUCH** has a large stainless steel tank capable of holding an item as long as 34cm in length. There are a range of optional accessories available to suit your every need. The **9020 TOUCH** has an easy to use drainage valve, making it simple to empty the dirty water from the tank.

WWW.PARTOSHAR.COM

Features:

- Large 6L stainless steel tank
- 300W total power
- Touch-screen control panel
- Drainage valve
- 2 x industrial transducers
- 2 x ceramic heaters 40°C 60°C
- 2 x cooling fans
- Solution usage timer
- Engineering grade plastic
- Quiet operation

Specification:

Model name	9020 TOUCH
Tank size	323 x 205 x 99mm
Timer settings	1 - 30 minute full range timer
Tank material	Stainless steel SUS304
Ultrasonic frequency	35,000Hz (35kHz)
Power consumption	300W Max
Power supply	AC 220- <mark>240</mark> V 50/60 Hz
Mains fuse	3A
Tank LxWxH	323 x 205 x 99mm
Outer Unit LxWxH	515 x 305 x 240mm
Weight	7.5kg
Optimal fill	3350ml
Maximum fill	6000ml
Snar	

WWW.PARTOSHAR.COM

Page 2