

## 9050 TOUCH (7500ml tank)



Ultrasonic cleaners function by producing sound waves that are transmitted into the tank and cleaning solution. These waves create millions of microscopic bubbles, which collapse or 'implode', releasing large amounts of energy, which scrub the surface clean. This process is called 'Cavitation'. These tiny bubbles create incredible cleaning results not only to the surface, but by penetrating the finer detail and recesses in surgical instruments and small items to ensure a professional clean prior to disinfection. The **9050 TOUCH** professional cleaner has three ultrasonic transducers to enable uniform distribution of ultrasonic waves and increases power output by 40%. The touch screen control panel of the **9050 TOUCH** has four simple to use keys, six timer settings and three temperature settings. The **9050 TOUCH** has a large stainless steel tank capable of holding an item as long as 37cm in length. There are a range of optional accessories available to suit your every need. The **9050 TOUCH** has an easy to use drainage valve, making it simple to empty the dirty water from the tank.

### Features:

- Large 7.5L stainless steel tank
- 410W total power
- Touch-screen control panel
- Drainage valve
- 3 x industrial transducers
- 3 x ceramic heaters 50°C - 60°C
- 3 x cooling fans
- Solid structural design
- Engineering grade plastic
- Quiet operation

### Specification:

Model name	9050 TOUCH
Tank size	331 x 238 x 105mm
Timer settings	1 - 30 minute full range timer
Tank material	Stainless steel SUS304
Ultrasonic frequency	35,000Hz (35kHz)
Power consumption	410W Max
Power supply	AC 220-240V 50/60 Hz
Mains fuse	3A
Tank LxWxH	331 x 238 x 105mm
Outer Unit LxWxH	541 x 337 x 277mm
Weight	9.8kg
Optimal fill	4300ml
Maximum fill	6000ml