SONIC 6MX (6000ml tank)



Page | 1

Ultrasonic cleaners function by producing sound waves that are transmitted into the tank and cleaning solution. These waves create millions of microscopic bubbles, which collapse or 'implode', releasing large amounts of energy, which scrub the surface clean. This process is called 'Cavitation'. These tiny bubbles create incredible cleaning results not only to the surface, but by penetrating the finer detail and recesses in jewellery and precision parts to restore them to their former glory.

Features:

- Large 6.0 litre stainless steel tank
- Rotary timer control 0-60 minutes with clear LCD display
- 240W high power performance

WWW.PARTOSHAR.COM

- Pulse/sweep
- Built in heater 0°C 80°C
- De-gas function
- Stainless steel basket & lid included
- Two-year warranty

Page | 2

Specification:

| Model name | SONIC 6MX | | | | |
|-----------------------|---------------------------|--|--|--|--|
| Tank volume | 6.0L | | | | |
| Tank dimensions (LWH) | 302 x 152 x 150mm | | | | |
| Tank material | 304 grade stainless steel | | | | |
| Ultrasonic frequency | 37,000Hz (37kHz) | | | | |
| Ultrasonic power | 240W + 200W heater | | | | |
| Ultrasonic power | Included | | | | |
| Drainage tap | Optional extra | | | | |
| Power supply | AC 220-240V 50Hz | | | | |
| Tank LxWxH | 302 x 152 x 150mm | | | | |
| Outer Unit LxWxH | 326 x 175 x 286mm | | | | |
| Basket LxWxH (top) | 295 x 145 x 130mm | | | | |
| Basket LxWxH (bottom) | 224 x 120 x 130mm | | | | |
| Weight | 4960 grams | | | | |
| Optimal fill | 4650ml | | | | |
| Maximum fill | 6000ml | | | | |
| Other features | Ultra-quiet operation | | | | |
| 2/1/1/ | Sealed Electronics | | | | |
| OT UUI | | | | | |

Comparison of Ultrasonic Baths:

| Sonic Model | 3D | 3MX | 4D | 4.5MX | 6D | 6MX |
|-------------|----|-----|----|-------|----|-----|
| Volume Size | 3L | 3L | 4L | 4.5L | 6L | 6L |
| (litre) | | | | | | |

WWW.PARTOSHAR.COM

| Tank | 238x138 | 238x138 | 302x152 | 238x138 | 302x152 | x152x302 |
|--------------------------|-----------|---------|---------|---------|---------|----------|
| Internal | x100 | x100 | x100 | x150 | x150 | 150 |
| Dimension | | | | | | |
| Operations | 40 | 37 | 40 | 37 | 40 | 37 |
| Frequency | | | | 7 , | | |
| (KHz) | | | | | 1 | |
| Ultrasonic | 120W | 160W | 120W | 160W | 180W | 240W |
| Power | | | | | | |
| Easy Clean Buttons | ٧ | × | ٧ | × | ٧ | × |
| | | | | | | |
| Easy Use Rotary Dials | · rqar | V | × | ٧ | × | V |
| D / | | | | | | |
| Pulse / Sweep | × | ٧ | × | ٧ | × | V |
| Drainage Trap | × | × | × | × | ٧ | √ |
| Degas | ٧ | ٧ | ٧ | ٧ | ٧ | ٧ |

Page 3

| Built in | | | | | | |
|-------------|---|---|---|---|---|---|
| Heater (0°C | | | | | | |
| − 80°C) | ٧ | ٧ | ٧ | V | ٧ | ٧ |
| | | | | | | |
| | | | | , | | |

Page

