

**Corrtest potentiostat /galvanostat / electrochemical workstation** consists of DDS arbitrary function generator, high power potentiostat/galvanostat, dual-channel correlation analyzer, dual-channel high-speed 16bit/high-precision 24bit AD converter and extension interfaces. Max. current is  $\pm 2A$ , potential range is  $\pm 10V$ . It can be used for various electrochemical fields such as corrosion, energy, material and electroanalysis. The current can be boosted up to 20A with a current booster.



## Applications

- Study of Energy materials (Li-ion battery, solar cell, fuel cell, supercapacitors), advanced functional materials
- Electrosynthesis, electroplating/electrodeposition, anode oxidation, electrolysis
- Corrosion study and corrosion resistance evaluation of metals; quick evaluation of corrosion inhibitors, coatings, and cathodic protection efficiency
- Electrocatalysis (HER, OER, ORR, CO<sub>2</sub>RR, NRR)


Specifications	
Support 2-, 3- or 4-electrode system	Potential and current range: Automatic
Potential control range: $\pm 10V$	Current control range: $\pm 2A$
Potential control accuracy: $0.1\% \times \text{full range} \pm 1mV$	Current control accuracy: $0.1\% \times \text{full range}$
Potential resolution: $10\mu V$ ( $>100Hz$ ), $3\mu V$ ( $<10Hz$ )	Current sensitivity: $1pA$
Rise time: $<1\mu S$ ( $<10mA$ ), $<10\mu S$ ( $<2A$ )	Reference electrode input impedance: $10^{12}\Omega    20pF$
Current range: $2nA \sim 2A$ , 10 ranges	Compliance voltage: $\pm 21V$
Maximum current output: $2A$	CV and LSV scan rate: $0.001mV \sim 10,000V/s$
CA and CC pulse width: $0.0001 \sim 65,000s$	Current increment during scan: $1mA @ 1A/ms$
Potential increment during scan: $0.076mV @ 1V/ms$	SWV frequency: $0.001 \sim 100 kHz$
DPV and NPV pulse width: $0.0001 \sim 1000s$	AD data acquisition: $16bit @ 1 MHz, 20bit @ 1 kHz$
DA Resolution: $16bit$ , setup time: $1\mu s$	Minimum potential increment in CV: $0.075mV$
IMP frequency: $10\mu Hz \sim 1MHz$	Low-pass filters: covering 8-decade
Operating System: Windows 2000/NT/XP/ 7/8/10	Interface: USB 2.0
Weight / Measurements: $6.5kg, 36.5 \times 30.5 \times 16 cm$	
EIS (Electrochemical Impedance Spectroscopy)	
Signal generator	
Frequency range: $10\mu Hz \sim 1MHz$	AC amplitude: $1mV \sim 2500mV$
DC Bias: $-10 \sim +10V$	Output impedance: $50\Omega$
Waveform: sine wave, triangular wave and square wave	Wave distortion: $<1\%$
Scanning mode: logarithmic/linear, increase/decrease	
Signal analyzer	
Integral time: minimum: $10ms$ or the longest time of a cycle	Maximum: $10^6$ cycles or $10^5s$
Measurement delay: $0 \sim 10^5s$	
DC offset compensation	
Potential automatic compensation range: $-10V \sim +10V$	Current compensation range: $-1A \sim +1A$
Bandwidth: 8-decade frequency range, automatic and manual setting	

## Techniques


Techniques		CS300M	CS310M	CS350M
<b>Stable polarization</b>	Open Circuit Potential (OCP)	√	√	√
	Potentiostatic (i-t curve)	√	√	√
	Galvanostatic	√	√	√
	Potentiodynamic(Tafel plot)	√	√	√
	Galvanodynamic	√	√	√
<b>Transient polarization</b>	Multi-Potential Steps	√	√	√
	Multi-Current Steps	√	√	√
	Potential Stair-Step (VSTEP)	√	√	√
	Galvanic Stair-Step (ISTEP)	√	√	√
<b>Chrono methods</b>	Chronopotentiometry (CP)	√	√	√
	Chronoamperometry (CA)	√	√	√
	Chronocoulometry (CC)	√	√	√
<b>Voltammetry</b>	Cyclic Voltammetry (CV)	√	√	√
	Linear Sweep Voltammetry (LSV)(i-v)	√	√	√
	Staircase Voltammetry (SCV) #	√		√
	Square wave voltammetry (SWV) #	√		√
	Differential Pulse Voltammetry (DPV)#	√		√
	Normal Pulse Voltammetry (NPV)#	√		√
	Differential Normal Pulse Voltammetry (DNPV)#	√		√
	AC voltammetry (ACV) #	√		√
<b>Amperometry</b>	Differential Pulse Amperometry (DPA)	√		√
	Double Differential Pulse Amperometry (DDPA)	√		√
	Triple Pulse Amperometry (TPA)	√		√
	Integrated Pulse Amperometric Detection (IPAD)	√		√
<b>EIS</b>	EIS vs Frequency (IMP)		√	√
	Galvanostatic EIS		√	√
	EIS vs Potential (IMPE) (Mott-Schottky)		√	√
	EIS vs Time (IMPT)		√	√
	Galvanostatic EIS vs Time		√	√
<b>Corrosion test</b>	Cyclic polarization curve (CPP)	√	√	√
	Linear polarization curve (LPR)	√	√	√
	Electrochemical Potentiokinetic Reactivation (EPR)	√	√	√
	Electrochemical Noise (EN)	√	√	√
	Zero resistance Ammeter (ZRA)	√	√	√
<b>Battery test</b>	Battery charge and discharge	√	√	√
	Galvanostatic charge and discharge (GCD)	√	√	√
	Potentiostatic Charging and Discharging(PCD)	√	√	√
	Potentiostatic Intermittent Titration Technique(PITT)	√	√	√
	Galvanostatic Intermittent Titration Technique(GITT)	√	√	√

## Application


**Corrosion:** Corrtest potentiostat includes all the electrochemical techniques for corrosion measurement such as OCP, polarization curve (potentiodynamic), EIS, Cyclic polarization CPP (passivation curve), Electrochemical Potentiokinetic Reactivation (EPR), Hydrogen diffusion test, ZRA, Electrochemical noise, etc. It can be used to study metal corrosion mechanism and corrosion resistance, and evaluate the coating durability and sacrificial anode current efficiency. It can also be used for rapid screening of corrosion inhibitors, fungicides, etc.



Polarization curves of Ti-alloy& stainless steel in 3%NaCl solution



EN of low-carbon steel in 0.05mol/LCl+0.1mol/LNaHCO<sub>3</sub>




It uses correlation integral algorithm and dual-channel over-sampling technique, and has strong anti-interference ability. The internal resistance of the instrument is up to 1013Ω. It's suitable for EIS measurements of high-impedance system (such as coating, concrete etc.)

Salt spray aging test of high impedance coating

## Energy


With techniques LSV, CV, galvanostatic charge and discharge (GCD), Constant potential/ current EIS, and precise IR compensation circuit, Corrtest potentiostats are widely used in supercapacitor, Li-ion batteries, sodium-ion batteries, fuel cell, Li-S batteries, solar cell, solid-state batteries, flow batteries, metal-air batteries etc. It is an excellent scientific tool for researchers in the fields of energy and materials.



CV curve of PPy supercapacitor in 0.5 mol/L H<sub>2</sub>SO<sub>4</sub> solution

## Electroanalysis


Corrtest potentiostat includes all the voltammetric methods such as NPV, DNPV, SWV, ACV, and can be used for fast analysis of the trace elements in the solution. Voltammetry stripping methods can do the Quantitative analysis according to the stripping peak current.




Stripping voltammetric curves in solution of different Pb<sup>2+</sup>, Cd<sup>2+</sup>, Zn<sup>2+</sup> concentration

## Electrocatalysis

- Corrtest potentiostat can measure the half-wave potential (ORR), overpotential (HER, OER) of the catalyst, and has the function of peak power density and energy density calculation.
- Long-term cyclic measurement for ORR, OER, HER, CO<sub>2</sub>RR by techniques such as cyclic voltammetry, potentiostatic, galvanostatic. Faraday efficiency can be measured with a bipotentiostat.
- Maximum current can be 20A and compliance voltage can be 30V, and with IR compensation technique, Corrtest potentiostat can precisely measure the overpotential of the electrode, which is a big advantage in electrocatalysis field.



LSV curve of catalysts in alkaline solution



## Sensors

Corrtest potentiostat can be used in the field of biosensors and chemical sensors, and many others.

Besides benchtop type, you can also consider our handheld potentiostat model CS100 (maximum current output  $\pm 45\text{mA}$ , potential range  $\pm 10\text{V}$ ) for sensors study. With the size of a mobile phone, it can be carried easily for lab and on-site use. Potential resolution is  $3\mu\text{V}$ , and current resolution can be  $1\text{pA}$ .

## Advantages


### Full floating

All Corrtest potentiostats / galvanostats are designed as full-floating, electrochemical study of working electrode connecting to earth, such as autoclave, metal part in bridge, concrete

### EIS

- Corrtest potentiostat uses correlation integral algorithm and dual-channel over-sampling technique, and has strong anti-interference ability. The internal resistance of the instrument is up to  $1013\Omega$ . It's suitable for EIS measurements of high-impedance system (such as coating, concrete etc.)

- With constant current carrier and DC bias technology, Corrtest potentiostat can be used for battery impedance measurement under charge and discharge state, suitable for ultra-low resistance system (such as 18650 battery, soft pack battery, battery core...)



EIS Accuracy

### Multi electrode system

- Support 2-, 3-, 4-electrode system, can be used to test battery internal resistance or 4-electrode thin film impedance measurement
- With Zero resistance ammeter for galvanic current measurement

### Combination test

CS studio software supports the combination test for various experiments to achieve flexible and unattended test. You can set the parameters for each experiment in advance, and set the intervals, wait time etc between each experiment.

No.	Name	Description
<input checked="" type="checkbox"/>	1	Start time
<input checked="" type="checkbox"/>	2	Start the cycle
<input checked="" type="checkbox"/>	3	Open Circuit Potential
<input checked="" type="checkbox"/>	4	Potentiostatic EIS (IMP)
<input checked="" type="checkbox"/>	5	Potentiodynamic (Tafel, LPR)
<input checked="" type="checkbox"/>	6	Wait
<input checked="" type="checkbox"/>	7	End the cycle

Combination Test: corrosion tests

No.	Name	Description
1	Cyclic Voltammety	Step1 E(V):-1 vsRef,Step2 E(V):1 vsRef,Scan Rate(mV/s):5,Freq(Hz):10,Cycl
2	Cyclic Voltammety	Step1 E(V):-1 vsRef,Step2 E(V):1 vsRef,Scan Rate(mV/s):10,Freq(Hz):20,Cyc
3	Cyclic Voltammety	Step1 E(V):-1 vsRef,Step2 E(V):1 vsRef,Scan Rate(mV/s):20,Freq(Hz):40,Cyc
4	Cyclic Voltammety	Step1 E(V):-1 vsRef,Step2 E(V):1 vsRef,Scan Rate(mV/s):50,Freq(Hz):100,Cy
5	Cyclic Voltammety	Step1 E(V):-1 vsRef,Step2 E(V):1 vsRef,Scan Rate(mV/s):100,Freq(Hz):200,C
6	Cyclic Voltammety	Step1 E(V):-1 vsRef,Step2 E(V):1 vsRef,Scan Rate(mV/s):200,Freq(Hz):400,C
7	Cyclic Voltammety	Step1 E(V):-1 vsRef,Step2 E(V):1 vsRef,Scan Rate(mV/s):500,Freq(Hz):1000

Combination Test: Pseudo capacitor tests


## High current option

- With the booster, the current can be boosted to 20A, which meets the requirement in fuel cell, power battery, electroplating, etc
- Can customize the instrument to be 30V high compliance voltage, which meets the test requirement in low-conductivity solutions (organic system, concrete system etc), especially suitable for carbon and nitrogen reduction study.



## Software development kit(SDK)

We can provide secondary development interfaces, API general interfaces and development examples, and can realize data call for Labview, C, C++, C#, VC and other program, which is convenient for secondary development and test methods customization.



## Real-time data storage


Experiment data can be stored in real time. Even if the test is interrupted by a power failure, the data will be automatically saved. The data is compatible with Excel, Origin, and can be directly opened in third-party software for data processing and curve drawing.

## Versatile data analysis

CS Studio is the software for Corrttest potentiostat for experiment control and data analysis. It can do: multi-parameter Tafel curve fitting, derivation, integration and peak height analysis of voltammetric curve, EIS equivalent circuit customization and impedance spectrum fitting, etc.

- Multi-parameters Polarization curve
- EIS fitting
- Electrochemical noise analysis
- Pseudo capacitance calculation
- GCD specific capacitance, efficiency

- Mott-Schottky plot analysis
- CV analysis




## Software Features

### Cyclic voltammetry:

CS studio software provides users a versatile smoothing/differential/ integration kit, which can complete the calculation of peak height, peak area and peak potential of CV curves. In CV technique, during the data analysis, there is function of selecting exact cycle(s) to show. You can choose to see a cycle or some cycles as you want. You can also export data or vector graph of an exact cycle or several cycles.


### Tafel plot and corrosion rate:

CS studio also provides powerful non-linear fitting on Butler-Volmer equation of polarization curve. It can calculate Tafel slope, corrosion current density, limitation current, polarization resistance, corrosion rate. It can also calculate the power spectrum density, noise resistance and noise spectrum resistance based on the EN measurements.



**Battery Test and analysis:**

charge & discharge efficiency, capacity, specific capacitance, charge & discharge energy.



**EIS analysis: Bode, Nyquist, Mott-Schottky plot**

During EIS data analysis, there is built-in fitting function to draw the custom equivalent circuit.

